



Polyamide 12 Gas Pipe Dimensions and Packaging

Yellow Polyamide 12 Gas Pipe—IPS Options

Size	Avg. OD (IN)	Min Wall (IN)	Weight (LBS/FT)	40FT Sticks/Pallet
1" - SDR 11	1.315	0.900	0.141	105
1-1/4" - SDR 11	1.660	0.900	0.237	105
1-1/2" - SDR 11	1.9	0.900	0.339	105
2" - SDR 11	2.375	0.216	0.598	105
3" - SDR 11	3.500	0.318	1.299	29
3" - SDR 13.5	3.500	0.259	1.076	29
4" - SDR 11	4.500	0.409	2.148	29
4" - SDR 13.5	4.500	0.333	1.779	29
6" - SDR 11	6.625	0.602	4.654	13
6" - SDR 13.5	6.625	0.491	3.860	13

Measures are approximate and may vary.

Yellow Polyamide 12 Gas Pipe—CTS Options

Size	Avg. OD (IN)	Max Wall	Weight (LBS/FT)	40FT Sticks/Pallet
1" - SDR 11	1.125	0.121	0.156	105
1-1/4" - SDR 11	1.375	0.121	0.194	105

Measures are approximate and may vary.

Product Standards: ASTM F2785-12

Pipe Materials: Polyamide 12 is cell class PA423 per ASTM D6779-17

Packaging: Stick lengths are 40' or 50'. Also available on reels.

Installation: Product can be installed per standard procedures and is fusion compatible per ASTM F2620.

